# NSN 5945-01-469-3035

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-469-3035

## **Overall Length:**

6.230 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.880 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

#### **Overall Height:**

3.090 inches

**Overall Width:** 

3.250 inches

**Environmental Protection:** 

Dustproof

**Unthreaded Mounting Hole Diameter:** 

0.199 inches single mounting facility

#### **End Application:**

## Spurdance class dd

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

## Mounting Facility Pattern:

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

1.00 seconds adjustable operate and release time and 10.00 seconds adjustable operate and release time

# Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

# Main Contact Maximum Voltage Rating In Volts:

120.0 ac

## **Terminal Type And Quantity:**

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

# NSN 5945-01-469-3035

Electromagnetic Relay - Page 2 of 2

Demilitarization:

No

Fiig:

A03300

