

View Online at <https://aerobasegroup.com/nsn/5945-01-469-9459>

**Overall Length:**

27.9 millimeters

**Overall Height:**

42.1 millimeters

**Overall Width:**

21.6 millimeters

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold flash

**Frequency In Hertz:**

Between 50.0 and 60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 plug-in terminal single mounting facility

**Operating Current Rating And Type:**

3.0 amperes ac single winding

**Operating Voltage Rating And Type At Specificationified Temp:**

120.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

0.8 amperes ac inductive load

**Main Contact Maximum Voltage Rating In Volts:**

250.0 ac

**Special Features:**

Contact resistance is 50 milliohms; operate and release times are 20 milliseconds ; insulation resistance is 100 megohms at 500 vdc; withstands dielectric strength of 2000 vac; vibration and shock resistant; operating ambient temperature is minus 55 deg. To plus 70 deg. C; relative humidity range is 35.0 to 85.0 percent; ul, csa, sev, and ce approved

**Precious Material:**

Silver and gold

**Terminal Type And Quantity:**

14 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300