

View Online at <https://aerobasegroup.com/nsn/5945-01-470-1862>

Overall Length:

50.0 millimeters

Overall Height:

81.6 millimeters

Overall Width:

40.0 millimeters

Frequency In Hertz:

Between 50.0 and 60.0

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac

Special Features:

This solid-state timer relay can be set to time ranges of 0.1 to 1.0 seconds, 1.0 to 10.0 seconds, 0.1 to 1.0 minutes, and 1.0 to 10.0 minutes by changing one of four white multiplier keys; time limit contact is dpdt; operating voltage is 85 to 110 percent of 120 vac; power consumption is 2 va ; insulation resistance is 100 megohms; withstands dielectric strength of 2000 vac; vibration and shock resistant; ambient operating temperature is minus 10 to plus 50 deg. C; ambient storage temperature is minus 25 to plus 80 deg. C; relative humidity type 45 to 85 percent; has power on and time-up indicators; standard surface mount can be flush mounted using adaptor p/n y92f-40, cage 61964

Terminal Type And Quantity:

8 standard tube base all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300