

View Online at <https://aerobasegroup.com/nsn/5945-01-477-5531>

**Environmental Protection:**

Hermetic

**Frequency In Hertz:**

Between 60.0 and 400.0

**Duty Type:**

Continuous

**Time Delay:**

0.0004 seconds fixed operate time

**Main Contact Load Current Rating At Maximum Rated Voltage:**

0.5 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 30.0 dc

**Special Features:**

Hermetically sealed; total submersibility; insulation resistance 1000.0 megohms min. At 500 vdc; breakdown voltage 500.0 volts rms 60.0 hertz between all mutually insulated points; temp. Range minus 55.0 to plus 71.0 deg. C; rated life 100000 operations min. At max. Rated load; terminals 0.030 in. Dia. Located on 0.200 in. Grid pattern; configuration 2 form c, double pole double throw; contact resistance 50.0 milliohms max. Initial measured at max. Rated load; sensitivity of 350.0 milliwatts at plus 25.0 deg. C; power 660.0 milliwatts at plus 25.0 deg. C; 24 volt coil; weight is 0.035 ounces

**Precious Material And Location:**

Contacts gold and contacts silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300