

View Online at <https://aerobasegroup.com/nsn/5945-01-480-9530>

Thread Class:

2a mounting facility stud

Thread Direction:

Right-hand mounting facility stud

Body Style:

Double ended actuator

Thread Length:

0.361 inches mounting facility stud

Body Diameter:

1.156 inches

Body Height:

0.719 inches

Case Material:

Zinc

Case Surface Treatment:

Dichromate

Actuator Diameter:

0.156 inches

End Application:

Stv camera sy wsd: generator set, diesel engine, 15kw, 400hz, mep113a

Inclosure Type:

Fully enclosed

Magnetic Coil Quantity:

1

Electrical Resistance:

3.16 ohms

Duty Type:

Continuous and pulse

Terminal Location:

Circumference

Electric Power Rating:

Between 7.0 watts and 140.0 watts

Voltage Rating In Volts:

Between 4.5 ac and 20.0 ac

Mounting Facility Type And Quantity:

2 threaded stud

Torque Rating And Type:

0.30 inch-pounds end

Thready Qty Per Inch (tpi):

48 mounting facility stud

Actuator Stroke Type:

Rotary

Power Takeoff Connection Type:

Plain

Energizing Stroke Maximum Length:

0.025 inches

Thread Size:

0.099 inches mounting facility stud

Mounting Facility Pattern:

Two position in-line

Rotation Direction And Energizing Stroke In Angular Deg:

45.0 counterclockwise

Thread Tolerance Class:

2a external mounting facility stud

Test Data Document:

72314-1425pd0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc mounting facility stud

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0