

View Online at <https://aerobasegroup.com/nsn/5945-01-480-9530>

**Thread Class:**

2a mounting facility stud

**Thread Direction:**

Right-hand mounting facility stud

**Body Style:**

Double ended actuator

**Thread Length:**

0.361 inches mounting facility stud

**Body Diameter:**

1.156 inches

**Body Height:**

0.719 inches

**Case Material:**

Zinc

**Case Surface Treatment:**

Dichromate

**Actuator Diameter:**

0.156 inches

**End Application:**

Stv camera sy wsd: generator set, diesel engine, 15kw, 400hz, mep113a

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Electrical Resistance:**

3.16 ohms

**Duty Type:**

Continuous and pulse

**Terminal Location:**

Circumference

**Electric Power Rating:**

Between 7.0 watts and 140.0 watts

**Voltage Rating In Volts:**

Between 4.5 ac and 20.0 ac

**Mounting Facility Type And Quantity:**

2 threaded stud

**Torque Rating And Type:**

0.30 inch-pounds end

**Thready Qty Per Inch (tpi):**

48 mounting facility stud

**Actuator Stroke Type:**

Rotary

**Power Takeoff Connection Type:**

Plain

**Energizing Stroke Maximum Length:**

0.025 inches

**Thread Size:**

0.099 inches mounting facility stud

**Mounting Facility Pattern:**

Two position in-line

**Rotation Direction And Energizing Stroke In Angular Deg:**

45.0 counterclockwise

**Thread Tolerance Class:**

2a external mounting facility stud

**Test Data Document:**

72314-1425pd0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc mounting facility stud

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A134a0