

View Online at <https://aerobasegroup.com/nsn/5945-01-481-0579>

**Overall Length:**

2.810 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.625 inches single mounting facility

**Overall Height:**

2.385 inches

**Overall Width:**

1.100 inches

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.156 inches single mounting facility

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 unthreaded hole single mounting facility

**Features Provided:**

Coil voltage suppression and polarized

**Mounting Facility Pattern:**

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:**

1 pole, double throw, double break/double make, permanent jumper, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

55.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Test Data Document:**

81349-mil-prf-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 threaded stud all functions

**Specification Data:**

81349-mil-prf-6106/15 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-6106 spec.