

View Online at <https://aerobasegroup.com/nsn/5945-01-482-4727>

Overall Length:

0.280 inches

Overall Diameter:

0.370 inches

Environmental Protection:

Shock proof and vibration proof and hermetic

Winding Quantity:

2

Coil Quantity:

1

Winding Dc Resistance Rating:

500.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

Features Provided:

Latching contacts and polarized

Nonpile-up Main Contact Arrangement:

2 pole, double throw, both positions maintained

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc resistive load and 500.0 milliamperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate level of 1.0 percent per 10, 000 cycles

Test Data Document:

81349-mil-prf-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

9 pin all functions

Specification Data:

81349-mil-prf-39016/12 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-39016 spec.