

View Online at <https://aerobasegroup.com/nsn/5945-01-484-6413>

Overall Length:

0.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.200 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.200 inches single mounting facility

Overall Height:

0.410 inches

Overall Width:

0.410 inches

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

700.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

8 printed circuit terminal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load and 0.3 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire lead all functions

Specification Data:

81349-mil-r-39016/6-109I government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300