

View Online at <https://aerobasegroup.com/nsn/5945-01-485-6815>

Overall Length:

0.370 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.100 inches single mounting facility

Overall Height:

0.398 inches

Overall Width:

0.335 inches

Overall Diameter:

0.275 inches

Environmental Protection:

Hermetic

End Application:

An/bsy-2 depo; feat g reverse polarity on coil terminals will destroy diode; feat g failure rate is 0.1 per 10, 000 cycles

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

2.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc resistive load and 250.0 milliamperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-prf-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 pin all functions

Specification Data:

81349-mil-prf-39016/23-030p government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300

Mil-std (military Standard):

Mil-prf-39016 spec.