

View Online at <https://aerobasegroup.com/nsn/5945-01-486-0224>

Overall Length:

1.025 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

1.025 inches

Overall Width:

1.010 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Hermetic

End Application:

End item

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

63.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 slotted hole single mounting facility

Features Provided:

Polarized and coil voltage suppression

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Special Features:

Failure rate is 1.0 percent per 10, 000 cycles

Test Data Document:

81349-mil-prf-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

14 wire hook all functions

Specification Data:

81349-mil-prf--83536/16-016m government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-83536 spec.