NSN 5945-01-494-4263

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-494-4263

Overall Length:

| Overall Length: |
|---|
| 4.520 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.750 inches single mounting facility |
| Overall Width: |
| 2.570 inches |
| End Application: |
| Electrical; mts |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 6 bracket single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.20 seconds adjustable release time and 200.00 seconds adjustable release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 125.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 125.0 dc |
| Special Features: |
| Time delay is dial calibrated in linear increments |
| Terminal Type And Quantity: |
| 8 screw all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

Fiig:

A03300