NSN 5945-01-495-7660

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-495-7660

Overall I	_enath:

1.025 inches

Overall Height:

1.125 inches

Overall Width:

0.525 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Hermetic

End Application:

Nsn 2350-01-354-5657; carrier command post

Frequency In Hertz:

Between 50.0 and 400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc lamp load and 2.0 amperes ac lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Failure rate 0.1 percent per 10, 000 cycles

Test Data Document:

81349-mil-prf-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-prfm-83536/11-009p government specification

Shelf Life:

N/a

NSN 5945-01-495-7660

Electromagnetic Relay - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-83536 spec.