NSN 5945-01-496-9659

Electromagnetic Relay - Page 1 of 2

Fiig: A03300



View Online at https://aerobasegroup.com/nsn/5945-01-496-9659

view Online at https://aerobasegroup.com/nsi//3343-01-430-3033
Overall Length:
0.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.100 inches single mounting facility
Overall Height:
0.375 inches
Overall Width:
0.335 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
3200.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 printed circuit terminal single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
1.0 amperes dc resistive load
Special Features:
Failure rate of 1.0 percent per 10, 000 cycles
Test Data Document:
31349-mil-prf-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 wire lead all functions
Specification Data:
31349-mil-prf-39016/41-044m government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5945-01-496-9659

Electromagnetic Relay - Page 2 of 2



Mil-std (military Standard):

Mil-prf-39016 spec.