NSN 5945-01-500-4390

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-01-500-4390

Tiew Offiline at https://defobasegroup.com/his//3945-01-300-4330
Overall Length:
Between 0.783 inches and 0.807 inches
Overall Height:
Between 0.527 inches and 0.575 inches
Overall Width:
Between 0.421 inches and 0.445 inches
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Coil Quantity:
Duty Type:
Continuous
Mounting Facility Type And Quantity:
Sterminal single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Fime Delay:
0.000005 seconds fixed operate and release time
Main Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
5.6 dc
Energizing Element Power Rating:
300.0 milliwatts
Special Features:
voltage 12.0 volts; pick up voltage 9.6 volts; drop-out voltage 1.2 volts; operating current 25.0 milliamps; coil resistance 432.0 ohms t
528.0 ohms; operating speed 30 cycles per minute; operating temperature range minus 40.0 to plus 65.0 degrees c; contact resistance
30.0 milliohms; switching power 150.0 watts
Precious Material And Location:
Ferminal surfaces gold and terminals silver
Precious Material:
Gold and silver
Ferminal Type And Quantity:
6 pin all functions
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No

Fiig: A03300