

View Online at <https://aerobasegroup.com/nsn/5945-01-509-0758>

**Overall Length:**

0.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.100 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.100 inches single mounting facility

**Overall Height:**

0.375 inches

**Overall Width:**

0.335 inches

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

800.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 printed circuit terminal single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Special Features:**

Failure rate 1.0 percent per 10, 000 operations; reverse polarity on coilterminals will destroy diode

**Test Data Document:**

81349-mil-prf-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire lead all functions

**Specification Data:**

81349-mil-prfm-39016/42-043m government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300

**Mil-std (military Standard):**

Mil-prf-39016 spec.