# NSN 5945-01-511-5051

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-511-5051

## **Overall Length:**

1.103 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.446 inches single mounting facility

## **Overall Height:**

1.718 inches

## **Overall Width:**

1.446 inches

#### **Environmental Protection:**

Shock proof

#### **Unthreaded Mounting Hole Diameter:**

0.150 inches single mounting facility

#### **End Application:**

Los angeles class ssn

#### Winding Quantity:

1

## Coil Quantity:

1

## Winding Dc Resistance Rating:

290.0 ohms single winding

## Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

#### Mounting Facility Pattern:

Rectangular single mounting facility

#### **Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

## Main Contact Maximum Voltage Rating In Volts:

28.0 dc

#### **Test Data Document:**

81349-mil-prf-83536/32 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

9 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A03300

## NSN 5945-01-511-5051

Electromagnetic Relay - Page 2 of 2

Mil-std (military Standard):

Mil-prf-83536 spec.

