

View Online at <https://aerobasegroup.com/nsn/5945-01-521-3553>

Overall Length:

1.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.396 inches single mounting facility and 1.446 inches single mounting facility

Overall Height:

1.660 inches

Overall Width:

1.025 inches

Mounting Slot Width:

0.150 inches single mounting facility

Environmental Protection:

Hermetic

End Application:

E/i 7386143 (53711) vdsdr canister assembly. Rmv

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

280.0 ohms single winding and 300.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Features Provided:

Coil voltage suppression and polarized

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.626 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Special Features:

Temperature range: -65 to +125 degrees c; altitude : 80, 000 ft.

Terminal Type And Quantity:

4 solder stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300