

View Online at <https://aerobasegroup.com/nsn/5945-01-521-3553>

**Overall Length:**

1.718 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.396 inches single mounting facility and 1.446 inches single mounting facility

**Overall Height:**

1.660 inches

**Overall Width:**

1.025 inches

**Mounting Slot Width:**

0.150 inches single mounting facility

**Environmental Protection:**

Hermetic

**End Application:**

E/i 7386143 (53711) vdsdr canister assembly. Rmv

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

280.0 ohms single winding and 300.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Features Provided:**

Coil voltage suppression and polarized

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

0.626 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

20.0 amperes dc motor load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Special Features:**

Temperature range: -65 to +125 degrees c; altitude : 80, 000 ft.

**Terminal Type And Quantity:**

4 solder stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300