NSN 5945-01-523-7203

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-523-7203

Overa	11 1	and	ıth.
Overa	II L	.enc	auı.

Between 3.190 inches and 3.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.865 inches single mounting facility and 2.885 inches single mounting facility

Overall Height:

Between 2.210 inches and 2.330 inches

Overall Width:

Between 1.480 inches and 1.600 inches

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

End Application:

E/i 7386040 (53711) pwr distribution j-box assembly, rmv; wsd: an/wld- (v) remote mine hunting system

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally closed, double break, momentary action

Operating Current Rating And Type:

0.3 amperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Special Features:

Gasket sealed, vented side stable; sperating temp: -55 to +85 degrees c; terminal studs: 2x 10-32 unf-2a and 2x 6-32 unc-2a

Terminal Type And Quantity:

4 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5945-01-523-7203

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300