## NSN 5945-01-523-7217

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-523-7217

#### **Overall Length:**

Between 3.690 inches and 3.810 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.190 inches single mounting facility and 3.310 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.940 inches single mounting facility and 2.060 inches single mounting facility

#### **Overall Height:**

2.930 inches

#### **Overall Width:**

Between 2.440 inches and 2.560 inches

#### **Unthreaded Mounting Hole Diameter:**

0.191 inches single mounting facility and 0.206 inches single mounting facility

#### **End Application:**

E/i 7386040 (53711) pwr distribution j-box assembly, rmv; wsd: an/wld- (v) remote mine hunting system

## Winding Quantity:

1

#### **Coil Quantity:**

## Winding Dc Resistance Rating:

60.0 ohms single winding

## **Duty Type:**

Continuous

#### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

## **Nonpile-up Main Contact Arrangement:**

1 pole, single throw, normally open, momentary action

## Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

400.0 amperes dc resistive load

### **Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

#### **Special Features:**

Gasket sealed, vented; operating temp: -55 to +125 deg. C; terminal studs: 2x 3/8-24 unf-2a and 2x 8-32 unc-2a

#### **Terminal Type And Quantity:**

4 threaded stud all functions

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5945-01-523-7217

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300