# NSN 5945-01-524-2084

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-524-2084

# **Overall Length:**

3.130 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility

#### **Overall Diameter:**

2.500 inches

# **Environmental Protection:**

Hermetic

### **Unthreaded Mounting Hole Diameter:**

0.168 inches single mounting facility and 0.175 inches single mounting facility

#### **End Application:**

Alofts sonar system, model 980 (v1)

# Winding Quantity:

1

#### **Coil Quantity:**

# Winding Dc Resistance Rating:

180.0 ohms single winding and 220.0 ohms single winding

# **Duty Type:**

Continuous

#### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

# **Pile-up Main Contact Form Arrangement:**

Зс

# **Mounting Facility Pattern:**

Rectangular single mounting facility

#### Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes dc motor load

# **Main Contact Maximum Voltage Rating In Volts:**

29.0 dc

#### **Product Name:**

Contactor 60 amp

# **Terminal Type And Quantity:**

13 threaded stud energizing element and contacts

# **Specification Data:**

81349-mil-prf-6106 government specification

# Shelf Life:

N/a

# NSN 5945-01-524-2084

Electromagnetic Relay - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-6106 spec.