

View Online at <https://aerobasegroup.com/nsn/5945-01-529-6831>

Overall Length:

3.700 inches

Overall Height:

1.600 inches

Overall Width:

2.180 inches

Mounting Slot Width:

0.172 inches single mounting facility

End Application:

E/i 04s004wt (31px6), dual generator, main switchboard

Frequency In Hertz:

Between 50.0 and 60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

480.0 volts ac 40 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac

Special Features:

Rinavy-relay, phase sequence; operating voltage range: 208-480 vac +/-15%; response time: 200 msec. Approx; operating temp range: 0 to 55 degrees c; total apparent power: 11 va @ 480 vac; glass filled valox surface mounted

Terminal Type And Quantity:

6 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300