

View Online at <https://aerobasegroup.com/nsn/5945-01-530-0346>

Overall Length:

2.660 inches

Overall Diameter:

0.520 inches

Case Material:

Metal and plastic

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

End Application:

Panel assembly, high volume

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

43.0 ohms single winding and 77.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 bracket single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

2.715 cubic inches

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Time Delay:

0.01 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load and 12.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

9000.0 ac and 9000.0 dc

Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 wire lead all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A03300