

View Online at <https://aerobasegroup.com/nsn/5945-01-530-0346>

**Overall Length:**

2.660 inches

**Overall Diameter:**

0.520 inches

**Case Material:**

Metal and plastic

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**End Application:**

Panel assembly, high volume

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

43.0 ohms single winding and 77.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 bracket single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

2.715 cubic inches

**Nonpile-up Main Contact Arrangement:**

1 pole, double throw, one position momentary

**Time Delay:**

0.01 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

12.0 amperes ac resistive load and 12.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

9000.0 ac and 9000.0 dc

**Test Data Document:**

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

1 wire lead all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A03300