

View Online at <https://aerobasegroup.com/nsn/5945-01-531-6836>

Overall Length:

1.280 inches

Overall Height:

0.640 inches

Overall Width:

0.850 inches

Mounting Slot Width:

0.133 inches single mounting facility

Environmental Protection:

Cold resistant and heat resistant and shock resistant and vibration resistant

End Application:

An/bqq-1 (v)6 unit 4150 trident, acoma jct box; wsd: ohio class ssbn (trident)

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

360.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.062 inches single mounting facility and 1.078 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Test Data Document:

81349-mil-prf-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

9 pin all functions

Specification Data:

81349 - -83536/21-022m government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-83536 spec.