

View Online at <https://aerobasegroup.com/nsn/5945-01-531-6836>

**Overall Length:**

1.280 inches

**Overall Height:**

0.640 inches

**Overall Width:**

0.850 inches

**Mounting Slot Width:**

0.133 inches single mounting facility

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and vibration resistant

**End Application:**

An/bqq-1 (v)6 unit 4150 trident, acoma jct box; wsd: ohio class ssbn (trident)

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

360.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.062 inches single mounting facility and 1.078 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-prf-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

9 pin all functions

**Specification Data:**

81349 - -83536/21-022m government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-83536 spec.