## NSN 5945-01-537-0135

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-537-0135

view Offiline at https://acrobasegroup.com/histr/0940-01-007-0100
Thread Class:
2a single mounting facility
Overall Length:
2.560 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.000 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.875 inches single mounting facility
Overall Height:
3.980 inches
Overall Width:
1.310 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Frequency In Hertz:
400.0
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc

Special Features:

Over-under voltage relay;

## NSN 5945-01-537-0135

Electromagnetic Relay - Page 2 of 2



<b>Special</b>	<b>Test</b>	<b>Featur</b>	es
----------------	-------------	---------------	----

Army will only use mfg - parko electric

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

10 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300