

View Online at <https://aerobasegroup.com/nsn/5945-01-537-0135>

Thread Class:

2a single mounting facility

Overall Length:

2.560 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches single mounting facility

Overall Height:

3.980 inches

Overall Width:

1.310 inches

Case Material:

Metal

Environmental Protection:

Dustproof

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Over-under voltage relay;

Special Test Features:

Army will only use mfg - parko electric

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300