

View Online at <https://aerobasegroup.com/nsn/5945-01-549-5253>

**Overall Length:**

1.280 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.062 inches single mounting facility and 1.078 inches single mounting facility

**Overall Height:**

0.810 inches

**Overall Width:**

0.410 inches

**Mounting Slot Width:**

0.133 inches single mounting facility

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**End Application:**

Airframe for 3mh60rx

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

500.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

2 slotted hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Cubic Measure:**

0.430 cubic inches

**Mounting Facility Pattern:**

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.004 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac lamp load and 1.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Special Features:**

Failure rate of 3.0 percent per 10, 000 cycles

**Terminal Type And Quantity:**

8 pin all functions

**Specification Data:**

81349 - mil-prf-83536/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300

**Mil-std (military Standard):**

Mil-prf-83536 spec.