

View Online at <https://aerobasegroup.com/nsn/5945-01-554-6085>

**Overall Length:**

1.280 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.070 inches single mounting facility

**Overall Height:**

0.410 inches

**Overall Width:**

0.810 inches

**Mounting Slot Width:**

0.133 inches single mounting facility

**Environmental Protection:**

Hermetic

**End Application:**

Universal weapons launcher (uwl) bay 1, 2, and 3; wsd: virginia class submarine, ssn-774

**Failure Rate Suffix Letter:**

P

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

440.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 slotted hole single mounting facility

**Mounting Facility Pattern:**

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Special Features:**

Navy-relay assembly; horizontal flange mount (hfm)

**Test Data Document:**

81349-mil-prf-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire hook all functions

**Specification Data:**

81349-mil-prf-83536/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-83536 spec.