

View Online at <https://aerobasegroup.com/nsn/5945-01-565-3817>

**Overall Length:**

1.280 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.070 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches single mounting facility

**Overall Height:**

0.640 inches

**Overall Width:**

0.810 inches

**Mounting Slot Width:**

0.133 inches single mounting facility

**Environmental Protection:**

Hermetic

**End Application:**

Swbd assembly 708675-101-1sf-ddgxx, 708677-101-2sf-ddgxx, swbd, pwr distrn

**Failure Rate Suffix Letter:**

L

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

70.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 slotted hole single mounting facility

**Features Provided:**

Polarized and coil voltage suppression

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

0.250 inches single mounting facility and 0.425 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 85 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes dc motor load and 3.0 amperes ac motor load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Special Features:**

Raised vertical flange mount (rvfm)

**Test Data Document:**

81349-mil-prf-83536 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

14 pin all functions

**Specification Data:**

81349-mil-prf-83536/5 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-83536 spec.