

View Online at <https://aerobasegroup.com/nsn/5945-01-574-5843>

**Overall Length:**

0.375 inches

**Overall Height:**

0.780 inches

**Overall Width:**

0.375 inches

**Overall Diameter:**

0.335 inches

**Environmental Protection:**

Hermetic

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

50.0 ohms single winding

**Duty Type:**

Continuous

**Time Delay:**

0.00 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

5.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Special Features:**

Failure rate level 3 percent per 10, 000 cycles; spacer mounting pad thickness is 0.014 inches

**Test Data Document:**

81349-mil-prf-39016/18h specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-prf-39016 spec.