

View Online at <https://aerobasegroup.com/nsn/5945-01-600-1354>

Overall Length:

3.03 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.32 inches single mounting facility

Overall Height:

2.56 inches

Overall Width:

2.16 inches

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

End Application:

Support av8 aircraft

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

Rectangular single mounting facility

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Product Name:

Drawing: contactor - spdt 100 amp, 28vdc sidestable

Special Features:

S central studs are 1/4-28 unf-2a; 2 near lower edge: polarized: 6-32 unc-2a; bottom is insulation plate: glass filled polyester; terminals are glass seal copper core stainless (nickel plated per qq-n-290); cover: aluminum 6061 (nickel plate); base header: brass (nickel plate); continuous cycle

Terminal Type And Quantity:

5 threaded stud contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A03300