

View Online at <https://aerobasegroup.com/nsn/5945-01-600-1354>

**Overall Length:**

3.03 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.625 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.32 inches single mounting facility

**Overall Height:**

2.56 inches

**Overall Width:**

2.16 inches

**Unthreaded Mounting Hole Diameter:**

0.196 inches single mounting facility

**End Application:**

Support av8 aircraft

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Features Provided:**

Polarized

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Product Name:**

Drawing: contactor - spdt 100 amp, 28vdc sidestable

**Special Features:**

S central studs are 1/4-28 unf-2a; 2 near lower edge: polarized: 6-32 unc-2a; bottom is insulation plate: glass filled polyester; terminals are glass seal copper core stainless (nickel plated per qq-n-290); cover: aluminum 6061 (nickel plate); base header: brass (nickel plate); continuous cycle

**Terminal Type And Quantity:**

5 threaded stud contacts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A03300