

View Online at <https://aerobasegroup.com/nsn/5945-01-626-6018>

**Overall Length:**

0.562 inches

**Overall Height:**

0.370 inches

**Overall Width:**

0.370 inches

**Environmental Protection:**

Hermetic and shock resistant

**Fragility Factor:**

Delicate

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

3.3 kilohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 printed circuit terminal single mounting facility

**Mounting Facility Pattern:**

Circular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

9.5 milliamperes dc single winding

**Time Delay:**

0.007 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Product Name:**

Teledyne established reliability relay series 432

**Special Features:**

432t dpdt relay with internal transistor driver and coil transient suppression diode

**Precious Material And Location:**

Contact finish gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

10 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300