

View Online at <https://aerobasegroup.com/nsn/5945-01-626-6018>

Overall Length:

0.562 inches

Overall Height:

0.370 inches

Overall Width:

0.370 inches

Environmental Protection:

Hermetic and shock resistant

Fragility Factor:

Delicate

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

3.3 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

Mounting Facility Pattern:

Circular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

9.5 milliamperes dc single winding

Time Delay:

0.007 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Product Name:

Teledyne established reliability relay series 432

Special Features:

432t dpdt relay with internal transistor driver and coil transient suppression diode

Precious Material And Location:

Contact finish gold

Precious Material:

Gold

Terminal Type And Quantity:

10 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300