

View Online at <https://aerobasegroup.com/nsn/5950-00-001-6545>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.938 inches

Body Width:

3.375 inches

Body Height:

5.250 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

3.0 amperes dc single component 3rd secondary

Winding Operating Voltage:

8.50 ac volts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0