

View Online at <https://aerobasegroup.com/nsn/5950-00-003-2536>

Reliability Indicator:

Not established

Overall Length:

Between 4.656 inches and 4.718 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.484 inches single mounting facility single center group and 3.516 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.734 inches single mounting facility single center group and 2.766 inches single mounting facility single center group

Overall Height:

Between 6.251 inches and 6.437 inches

Overall Width:

Between 3.844 inches and 3.906 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

300.0 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

12.0 amperes ac single component single secondary

Winding Operating Voltage:

25.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0