

View Online at <https://aerobasegroup.com/nsn/5950-00-003-4734>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.590 inches single mounting facility single center group and 2.720 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.720 inches single mounting facility single center group and 2.780 inches single mounting facility single center group

Mounting Hole Diameter:

0.215 inches single group and 0.223 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.740 inches

Body Width:

3.880 inches

Body Height:

4.400 inches

End Application:

Usns stalwart class tagos; supply class aoe; cimmaron class ao; stream (std. Tensioned replenishment at sea method); avenger class mcm; deck machinery; wasp class lhd; tarawa class lha; spruance class dd (963); austin ship class lpd-4 amphibious transport docks

Inclosure Type:

Partially enclosed, double shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

869.6 milliamperes ac single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

440.00 ac volts single component single primary

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0