

View Online at <https://aerobasegroup.com/nsn/5950-00-003-4734>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.590 inches single mounting facility single center group and 2.720 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.720 inches single mounting facility single center group and 2.780 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.215 inches single group and 0.223 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

4.740 inches

**Body Width:**

3.880 inches

**Body Height:**

4.400 inches

**End Application:**

Usns stalwart class tagos; supply class aoe; cimmaron class ao; stream (std. Tensioned replenishment at sea method); avenger class mcm; deck machinery; wasp class lhd; tarawa class lha; spruance class dd (963); austin ship class lpd-4 amphibious transport docks

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Bracket single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

869.6 milliamperes ac single component single secondary

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

440.00 ac volts single component single primary

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0