

View Online at <https://aerobasegroup.com/nsn/5950-00-004-0220>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facili type 2nd center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facili type 2nd center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta and delta-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

4.600 inches

Body Width:

3.880 inches

Body Height:

3.150 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 2nd group

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.164 inches all groupings

Winding Operating Current:

200.0 milliamperes ac single component single primary

Winding Operating Voltage:

22.60 ac volts single component 2nd secondary

Special Features:

One primary winding; five secondary windings

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0