

View Online at <https://aerobasegroup.com/nsn/5950-00-004-2071>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant and flame resistant

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.140 inches single mounting facility single center group and 1.160 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.090 inches single mounting facility single center group and 1.110 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.146 inches single group and 0.166 inches single group

**Inductance Type:**

Fixed

**Inductance Rating:**

9.00 millihenries single component single winding

**Frequency Rating:**

20.0 kilohertz single component

**Body Length:**

1.500 inches

**Body Width:**

1.450 inches

**Body Height:**

1.780 inches

**Maximum Operating Temp:**

85.0 degrees celsius

**Winding Quantity:**

1 single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Rating Method:**

Electrical single component single winding

**Winding Operating Current:**

2.0 amperes dc single component single winding

**Dc Resistance Rating In Ohms:**

0.500 single component single winding

**Test Data Document:**

82577-986056 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0