## **NSN 5950-00-006-0610**Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-00-006-0610             |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.187 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.187 inches single mounting facility single center group                 |
| Overall Height:   |
| 2.750 inches  |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure and core single component           |
| Body Length:  |
| 1.625 inches  |
| Body Width:   |
| 1.625 inches  |
| Body Height:  |
| 2.375 inches  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 2 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group   |
| Winding Operating Voltage:  |
| 8.00 ac volts single component single primary                             |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 6 wire hook   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure   |

Demilitarization:

No

## **NSN 5950-00-006-0610**Power Transformer - Page 2 of 2



Fiig:

A058b0