

View Online at <https://aerobasegroup.com/nsn/5950-00-006-4685>

Reliability Indicator:

Not established

Overall Length:

Between 5.000 inches and 5.060 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.240 inches single mounting facility single center group and 4.260 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.240 inches single mounting facility single center group and 2.260 inches single mounting facility single center group

Overall Height:

4.500 inches

Overall Width:

4.000 inches

Mounting Hole Diameter:

0.210 inches single group and 0.220 inches single group

Frequency Rating:

50.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Winding Operating Current:

20.0 amperes ac single component 2nd secondary

Winding Operating Voltage:

8.40 ac volts single component 1st secondary and 13.40 ac volts single component 1st secondary and 16.80 ac volts single component 1st secondary

Special Features:

2primary windings; 5secondary windings

Test Data Document:

57057-8892400014 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

19 solder stud and 3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0