

View Online at <https://aerobasegroup.com/nsn/5950-00-006-4685>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 5.000 inches and 5.060 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.240 inches single mounting facility single center group and 4.260 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.240 inches single mounting facility single center group and 2.260 inches single mounting facility single center group

**Overall Height:**

4.500 inches

**Overall Width:**

4.000 inches

**Mounting Hole Diameter:**

0.210 inches single group and 0.220 inches single group

**Frequency Rating:**

50.0 hertz single component and 420.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Maximum Operating Temp:**

85.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Bracket single group and unthreaded hole single group

**Winding Function And Quantity:**

2 primary single component and 5 secondary single component

**Winding Operating Current:**

20.0 amperes ac single component 2nd secondary

**Winding Operating Voltage:**

8.40 ac volts single component 1st secondary and 13.40 ac volts single component 1st secondary and 16.80 ac volts single component 1st secondary

**Special Features:**

2primary windings; 5secondary windings

**Test Data Document:**

57057-8892400014 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

19 solder stud and 3 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0