

View Online at <https://aerobasegroup.com/nsn/5950-00-007-9641>

Reliability Indicator:

Not established

Overall Length:

Between 0.240 inches and 0.350 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.200 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.400 inches single mounting facility single center group

Overall Height:

Between 0.140 inches and 0.285 inches

Overall Width:

Between 0.035 inches and 0.080 inches

Mounting Hole Diameter:

0.281 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

7.16 amperes ac single component 1st secondary

Winding Power Rating:

1.9 kilovolt-amperes single component all secondary

Winding Operating Voltage:

41.70 ac volts single component 1st secondary

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0