## NSN 5950-00-007-9641

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-007-9641

Reliability Indicator:
Not established
Overall Length:
Between 0.240 inches and 0.350 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.200 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.400 inches single mounting facility single center group
Overall Height:
Between 0.140 inches and 0.285 inches
Overall Width:
Between 0.035 inches and 0.080 inches
Mounting Hole Diameter:
0.281 inches single group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
6 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Winding Operating Current:
7.16 amperes ac single component 1st secondary
Winding Power Rating:
1.9 kilovolt-amperes single component all secondary
Winding Operating Voltage:
41.70 ac volts single component 1st secondary
Terminal Type And Quantity:
15 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## **NSN 5950-00-007-9641** Power Transformer - Page 2 of 2

Fiig: A058b0

