NSN 5950-00-008-2563

Reactor - Page 1 of 2

Reliability Indicator:

Not established



View Online at https://aerobasegroup.com/nsn/5950-00-008-2563

2.750 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.187 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.125 inches single mounting facility single center group Mounting Hole Diameter: 0.172 inches single group and 0.188 inches single group Inductance Type: Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a Unit Of Measure:	Overall Length:
2.187 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.125 inches single mounting facility single center group Mounting Hole Diameter: 0.172 inches single group and 0.188 inches single group Inductance Type: Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	2.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.125 inches single mounting facility single center group Mounting Hole Diameter: 0.172 inches single group and 0.188 inches single group Inductance Type: Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Center To Center Distance Between Mounting Facilities Parallel To Length:
Mounting Hole Diameter: 0.172 inches single group and 0.188 inches single group Inductance Type: Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	2.187 inches single mounting facility single center group
Mounting Hole Diameter: 0.172 inches single group and 0.188 inches single group Inductance Type: Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Center To Center Distance Between Mounting Facilities Parallel To Width:
Inductance Type: Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	1.125 inches single mounting facility single center group
Inductance Type: Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Mounting Hole Diameter:
Fixed Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	0.172 inches single group and 0.188 inches single group
Inductance Rating: 800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Inductance Type:
800.00 microhenries single component single winding Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Fixed
Frequency Rating: 60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Inductance Rating:
60.0 hertz single component Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	800.00 microhenries single component single winding
Body Length: 2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Frequency Rating:
2.000 inches Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	60.0 hertz single component
Body Width: 1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Body Length:
1.850 inches Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	2.000 inches
Body Height: 2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Body Width:
2.310 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	1.850 inches
Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Body Height:
1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	2.310 inches
Inclosure Type: Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Winding Quantity:
Fully enclosed Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	1 single component
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Inclosure Type:
4 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Fully enclosed
Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Mounting Facility Quantity:
Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	4 single group
Rating Method: Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Mounting Method:
Electrical single component single winding Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Flange single group and unthreaded hole single group
Winding Operating Current: 10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Rating Method:
10.0 amperes dc single component single winding Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Electrical single component single winding
Dc Resistance Rating In Ohms: 0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Winding Operating Current:
0.040 single component single winding Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	10.0 amperes dc single component single winding
Terminal Type And Quantity: 2 tab, solder lug Shelf Life: N/a	Dc Resistance Rating In Ohms:
2 tab, solder lug Shelf Life: N/a	0.040 single component single winding
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 tab, solder lug
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

NSN 5950-00-008-2563

Reactor - Page 2 of 2



Demi			

No

Fiig:

A058b0