

View Online at <https://aerobasegroup.com/nsn/5950-00-010-5392>

Reliability Indicator:

Not established

Turn Quantity:

14 single component single winding

Inductance Rating:

0.90 microhenries single component single winding and 1.90 microhenries single component single winding

Coil Form Type:

Hollow single component

Core Construction:

Powdered single component

Adjustment Device Drive Type:

Slotted screw single component

Body Length:

0.680 inches

Overall Diameter:

0.284 inches

End Application:

Wsd: iwo jima class lph; los angeles ssn (688); nimitz cvn; kidd ddg; emory s. Land as; cimmaron ao; wichita aor; sturgeon ssn (637); tarawa lha; mars tpafs 1; blue ridge lcc-19; electric test equipment-gpete; missile, air-to-air, phoenix (aim-54)

Inclosure Type:

Fully enclosed

Mounting Method:

Plug-in single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Winding Conductor Size:

0.01264 inches american wire gage single component single winding

Quality Factor:

50 single component single winding

Adjustment Method And Quantity:

1 adjustable core single component

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0